

Phelps Honey Wagon



PHW 500E

- Pump:** Cast aluminum pump to resist corrosion
12 in. Thermoplastic Diaphragm
50 gallons per minute
Will pump a 25 ft. head
Neoprene Flapper Valves
Self-priming
- Motor:** 1.5 H.P. single phase, 115/230-volt electric motor with manual reset overload
Weatherproof on/off switch
20 foot 115 VAC power cord
- Tank:** 500 Gallon Capacity Tank
Polyethylene plastic tank for long life with approx. 1/4 in. walls
Dimensions: 48 in. diameter | 75 in. length
Translucent tank to show content level
Tank is supported by a steel pan on a 5 in. steel channel frame
Large top lid for easy interior hose down
- Discharge:** Gravity drain with 3 in. rear discharge gate valve and cap
- Adapters:** RV Hose Adapter, fits all RV's
- Hose:** 50 ft. of 2 in. Hi Vac hose, very flexible, tough, lightweight and non-kinking
- Tongue:** 2 in. ball coupler
Side Wind Jack with Wheel (800 lbs. maximum)
- Axle:** Tandem axle - 3500 lbs. rating per axle
- Tires:** 175/80-13" tires
- Weight:** Approx. 1090 lbs
- Warranty:** One year warranty on trailer and tank
One year warranty for workmanship on pump and motor

158 Whiskey Springs Road

Dillsburg, PA 17019

Phone: 1-800-463-3707

www.phelpshoneywagon.com