

# Phelps Honey Wagon



## PHW 500G

- Pump:** Cast aluminum pump to resist corrosion  
12 in. Thermoplastic Diaphragm  
60 gallons per minute  
Will pump a 25 ft. head  
Neoprene Flapper Valves  
Self-priming
- Motor:** 3.5 H.P. Briggs & Stratton engine or 5.5 H.P. Honda engine
- Tank:** 500 Gallon Capacity Tank  
Polyethylene plastic tank for long life with approx. 1/4 in. walls  
Dimensions: 48 in. diameter | 75 in. length  
Translucent tank to show content level  
Tank is supported by a steel pan on a 5 in. steel channel frame  
Large top lid for easy interior hose down
- Discharge:** Gravity drain with 3 in. rear discharge gate valve and cap
- Adapters:** RV Hose Adapter, fits all RV's
- Hose:** 50 ft. of 2 in. Hi Vac hose, very flexible, tough, lightweight and non-kinking
- Tongue:** 2 in. ball coupler  
Side Wind Jack with Wheel (800 lbs. maximum)
- Axle:** Tandem axle - 3500 lbs. rating per axle
- Tires:** 175/80-13" tires
- Weight:** Approx. 1090 lbs
- Warranty:** One year warranty on trailer and tank  
One year warranty for workmanship on pump  
Engine has warranty by an authorized dealer:
- Honda - 2 years
  - Briggs & Stratton - 90 days

158 Whiskey Springs Road  
Dillsburg, PA 17019  
Phone: 1-800-463-3707

[www.phelpshoneywagon.com](http://www.phelpshoneywagon.com)